



High rejection

Low PIM

Low insertion loss

Duplex n105 663-703 / 612-652 MHz

Product number: ZEN – 500 – 200 – 39

RX	Frequency Range [MHz]	Requirement
Passband	663 – 703	
Return Loss	663 – 703	> 18 dB
Insertion Loss Max	663 – 703	< 1.0 dB
Rejection	612 – 652	> 75 dB

TX	Frequency Range [MHz]	Requirement
Passband	612 – 652	
Return Loss	612 – 652	> 18 dB
Insertion Loss Max	612 – 652	< 1.4 dB
Rejection	663 – 703	> 100 dB

Power	Average	Max 80 W (49 dBm)
	Peak	Max 2000 W (63 dBm)

Environmental	
Temperature range	-20 °C to +85 °C
Ingress Protection	IP63
Altitude	3000 m

Mechanical	
Dimensions	243 x 186 x 61 mm (excluding connectors) 305 x 186 x 61 mm (including connectors)
Connectors	4.3-10 (f)

Passive Intermodulation	2 x 43 dBm	< - 117 dBm < - 160 dBc
-------------------------	------------	----------------------------

High rejection

Low PIM

Low insertion loss

Duplex n105 663-703 / 612-652 MHz

Product number: ZEN - 500 - 200 - 39

