




High stop band rejection

Low insertion loss

High power handling

Diplexer B38A 2575 – 2615 MHz

Product number: ZEN – 500 – 200 – 47

Band pass filter	Frequency Range [MHz]	Requirement
Passband	2575 – 2615	
Return Loss	2575 – 2615	> 14 dB
Insertion Loss Max Typically	2575 – 2615	< 2.0 dB < 1.0 dB
Rejection	9 kHz – 2570	> 50 dB
Rejection	2620 – 4000	> 50 dB

Band stop filter	Frequency Range [MHz]	Requirement
Passband	9 kHz – 2570 2620 – 4000	
Return Loss	9 kHz – 2570 2620 – 4000	> 10 dB
Insertion Loss Max Typically	9 kHz – 2570 2620 – 4000	< 3.0 dB < 1.0 dB
Rejection	2575 – 2615	> 90 dB

Power	Average	max 200 W (53 dBm)
	Peak	max 2000 W (63 dBm)

Passive Intermodulation (PIM)	2 x 43 dBm	< - 117 dBm (< - 160 dBc)
-------------------------------	------------	--------------------------------

Mechanical		
Dimensions	360 x 183 x 41 mm (excluding connectors) 422 x 183 x 41 mm (including connectors)	
Connectors	4.3-10 (f)	



High stop band rejection

Low insertion loss

High power handling

Diplexer B38A 2575 – 2615 MHz

Product number: ZEN – 500 – 200 – 47



Environmental

Temperature range

+18 °C to +40 °C

Ingress Protection

IP63






High stop band rejection

Low insertion loss

High power handling

Diplexer B38A 2575 – 2615 MHz

Product number: ZEN – 500 – 200 – 47



BSF

